



Quality Through Innovation™



PROFESSIONAL WIRELESS CONFERENCE SYSTEM With Vocal Cut-Off

MC-990W Series



*Receiver Main Unit MC-990MW

1 YEAR WARRANTY
*Conditions Apply



*Chairman MC-990CW



*Delegate MC-990DW

KREZT.CO.ID

NOTE : Features and specifications are subject to change without notice. All images and illustrations are provided for information purposes only.

OVERALL SYSTEM FEATURES

- * Easy to set up
- * Support up to 1000 microphone units (5 microphones can be turned on simultaneously)
- * Multi-channels high & intermediate band frequency filtering
 - * Feedback eliminating technology
- * Built-in noise detecting circuit & TONE LOCK system
- * Up to 100m operating distance in perfect condition (60m in normal condition)
- * Support Video Function - with additional video processor (optional)

FEATURES

SPECIFICATION

Receiver Main Unit



*MC-990MW

Transmission method	UHF Wireless (one way)
Audio channel	5 (1 chairman, 4 delegates)
Carrier frequency band	500MHz- 950MHz
Modulation method	FM
Receiving sensitivity	-100dBm
Audio gain	=<20
Frequency response	50 Hz-15KHz
S/N Ratio	>85dB
T.H.D.	<0.8%
Power supply	DC12 - 15V =<1A
Signal covering range	Radius 60 meters
Consumption Rating	7W
Operating temperature range	-10 - 40 degree
Dimensions	485x355x85 mm
N.W	7 kg

Microphone

Delegate

- LCD display
- On/Off Key & indicator
- 3 function keys to set ID, control channel, volume level & battery status
- Power shut-off or standby mode when receiver is powered off



*MC-990DW

Chairman

- *including all the functions of the delegates unit
- Can be turned on at anytime
- Priority function: Vocal cut-off
- Chairman only mode



*MC-990CW

Transmission method	UHF Wireless (one way)
Audio channel	5 (1 chairman, 4 delegates)
Carrier frequency band	500MHz- 950MHz
Modulation method	FM
Maximum modulation	60KHz
Radiant power	=<+9dBm
Frequency deviation	<0.002
Frequency response	50Hz-15KHz
S/N Ratio	>85dB
T.H.D.	<0.8%
Power supply	DC3.7- 4.5V
Signal covering range	Radius 60 meters
Consumption rating	Standby : =<360mW Speaking : =<630mW
Operating temperature range	-10 - 40 degree
Dimensions	170x58x120 mm
N.W	0.7kg