



INTRODUCING
X **TREME** **160R** **4V**
FOUR VALVE



*Fastest compared to all oil & air cooled engine motorcycles in the 160cc segment as per internal testing.

THE FASTEST* 160CC IS HERE

A NEW RACE IS HERE

IT'S SHORT, BUT DEFINITELY NOT SWEET.
IT'S NOT FOR THE FAINT-HEARTED.

IT'S FOR THOSE WHO DO BURNOUTS
NOT TO SHOW OFF, BUT TO START OFF.

FOR THOSE WHO DON'T BLINK,
BUT LEAVE EVERYONE WIDE-EYED.

IT'S CALLED DRAG RACING,
AND THOSE WHO ACE IT,
ARE CALLED DRAGSTERS.

READY TO LIVE THE DRAGSTER LIFE?



**A NEW RACE
CALLED
DRAGSTERS**



THE FASTEST* 160CC IS HERE

*Fastest compared to all oil & air cooled engine motorcycles in the 160cc segment as per internal testing.

THE FASTEST RACE

Fast, as you know, is about to change. Xtreme 160R 4V's fastest acceleration will get you high on thrill and make objects in the rearview mirror disappear in a flash.

4V

FOUR VALVE

4-valve technology & best-in-class 5 Fin Oil Cooler deliver next level performance while maintaining thermal stability and engine refinement.



Fastest 0-60 | Fastest 0-100 | Fastest 0-Top Speed | Highest Top Speed

RIDE EASY RACE HARD



KYB USD Forks

37mm Dia for a
macho stance.

Bluetooth Connectivity

Never miss a call
or text alert.



Inverted LCD Display

Be it bright or dark.
For you, it'll be perfect.

All new Split Seat

Interchangeable with
single seat.



All LED Lights

Light up the road for
your fellow dragsters.

THE BEST IS NOW BETTER

Mono Shock Suspension

7 step adjustable, for pre-load.

Oil Cooler

For a thermally stable engine, even at high RPM.



Front & Rear Petal Disc Brakes

The safety of two.

130mm Radial Rear Tyre

Better stability, better grip.

Sporty Exhaust

For the sweet sound of victory.

STAY CONNECTED AS YOU RACE!

Hero **CONNECT 2.0**



LIVE TRACKING

Wander, but don't get lost.



REMOTE IMMOBILIZATION

Someone else on your seat? Not anymore.



VEHICLE DIAGNOSTIC

Before you race, have it all in place.



FIND MY BIKE

Let your phone spot your dragging partner.



PANIC ALERT

Help is just a click away.

+20 More Features



BRAG YOUR DRAG

CHOOSE FROM AN EXCITING RANGE OF COLOURS,
AND LET THE RACE BEGIN.



Blazing Sports Red
Standard variant



Matt Slate Black
Connect 2.0*



Neon Shooting Star
Pro variant



Matt Slate Black
Pro variant



A NEW RACE CALLED DRAGSTERS

SPECIFICATIONS

	SPECS	STANDARD VARIANT	PRO VARIANT
ENGINE	Engine Type	4 Stroke, Air-Oil Cooled, 4 Valve	4 Stroke, Air-Oil Cooled, 4 Valve
	Bore & Stroke	66.5 mm x 47.0 mm	66.5 mm x 47.0 mm
	Displacement (cm ³)	163.2	163.2
	Compression Ratio	10.1:1	10.1:1
	Max Power	16.9 Ps/12.4kW @ 8500rpm	16.9 Ps/12.4kW @ 8500rpm
	Max Torque	14.6 Nm @6500 rpm	14.6 Nm @6500 rpm
	Transmission Type	5 Speed Constant Mesh	5 Speed Constant Mesh
	Clutch Type	Multiplate Wet	Multiplate Wet
CHASSIS	Frame Type	Tubular Underbone Diamond Type	Tubular Underbone Diamond Type
	Swing Arm	Box type (50x30mm rectangle tube)	Box type (50x30mm rectangle tube)
SUSPENSION	Front Suspension Type	Standard Telescopic, 37mm Dia	KYB USD Forks, 37mm Dia
	Rear Suspension Type	7 Step Adjustable Monoshock	7 Step Adjustable Monoshock
BRAKES	Front Brake type	Disc 276 mm (Petal)	Disc 276 mm (Petal)
	Rear Brake Type	Disc 220 mm (Petal)	Disc 220 mm (Petal)
WHEELS & TYRES	Wheel Type	Alloy	Alloy
	Front Tyre Size	100/80 -17 (TL)	100/80 -17 (TL)
	Rear Tyre Size	130/70 R 17 (TL)	130/70 R 17 (TL)
ELECTRICALS	Lamps	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers
	Battery (V-Ah)	12 V-6AH (VRLA)	12 V-6AH (VRLA)
	Starting System	Self Start	Self Start
WEIGHT & DIMENSIONS	Overall Length (mm)	2029	2029
	Overall Width (mm)	793	793
	Overall Height (mm)	1052	1052
	Wheelbase (mm)	1333	1333
	Seat Height (mm)	795	795
	Ground Clearance (mm)	165	165
	Fuel Tank Capacity (L)	12	12
	Kerb Weight (kg)	144	145

Connected 2.0 Features available as a variant over Standard

THE FASTEST* 160CC IS HERE



heromotocorp.com



Hero MotoCorp



Hero MotoCorp



Hero MotoCorp



Hero MotoCorp

*Fastest compared to all oil & air cooled engine motorcycles in the 160cc segment as per internal testing.