

# CONNECTING ASPIRATIONS TO POSSIBILITIES

**STARBUS LP 913**



AC/Non AC

# STARBUS LP 913

## SPECIFICATIONS

### ENGINE

Type	Tata 697 TCIC E2
Engine	Capacity 5675 cc
Max. Power	128 Hp @ 2400 rpm
Torque	416Nm @ 1400 - 1700 rpm

### CLUTCH

Type	Single plate dry friction type
Outside Diameter	310 mm

### GEARBOX

Model	GBS - 40 Synchromesh
No. of Gears	5 F + 1 R

<b>STEERING</b>	Power steering
-----------------	----------------

### SUSPENSION

Type	Semi elliptical leaf spring at front and rear
Anti-roll Bar	At front and rear

### BRAKES

Service Brakes	Dual circuit full air S-cam brakes - ABS optional
Parking Brake	Spring actuated parking brake acting on rear wheels
Engine Exhaust Brake	Coupled with service brake
Front / Rear Type	Drum / Drum

### WHEELS & TYRES

Tyres	8.25 x 16 - 14 PR
No. of Wheels	Front: 2, Rear: 4, Spare: 1

<b>FUEL TANK</b>	160 Litres
------------------	------------

<b>ELECTRICAL SYSTEM</b>	24 Volts
--------------------------	----------

### PERFORMANCE

Max. Geared Speed in Top Gear	107 kmph
Max. Climbing Ability in 1st Gear	29%
Min. Turning Circle Diameter	17.5 m

### DIMENSIONS & WEIGHTS

Wheelbase	4920 mm
Track- Front / Rear	1665 mm / 1622 mm
Overall Bus Length	9300 mm
Overall Bus Width	2200 mm
Overall Height	3100 mm
Max. Permissible FAW	3000 kgs
Max. Permissible RAW	6000 kgs
Max. Permissible GVW	9000 kgs

<b>SEATING CAPACITY &amp; DOORS</b>	38+1 seats (2x2 layout) - 2 door, 36+1 seats (2x2 layout) - 1 door, 36 + 7 jump seats (2x2 layouts) - 1 door
-------------------------------------	--

<b>AC / Non AC</b>	Available in AC / Non AC
--------------------	--------------------------

Available in Left Hand Drive only



38 + 1 seats (2x2 layout)



36 + 1 seats (2x2 layout)



36 + 7 jump seats LP 913

### TATA MOTORS LIMITED

International Business, A Block, Shivsagar Estate,  
Dr A B Road, Worli, Mumbai 400018. India.

Tel : 91 22 67577200, Fax : 91 22 67577225 Website: [www.tatamotors.com](http://www.tatamotors.com)

Tata Motors reserves the right to change and vary the design, technical specifications at any time, without prior notice, as per the Company's policy of continuous product improvement. The illustrations may show accessories and items of optional equipment which are not part of standard specifications. Colours may vary slightly from those shown, owing to limitations of printing process.