



### Main

Range	ZENcelo
Product or component type	Switch
Load type	Inductive Fluorescent lamp Incandescent lamp
Colour tint	White

### Complementary

Device mounting	Flush Surface
Switch function	1-way
Rated current	20 A at 240 V AC 50/60 Hz 16 AX
Local signalling	Red neon with on indicator
Number of gangs	1 gang
Material	Polycarbonate, for base Brass, for metal parts Polycarbonate, for cover Steel, for metal parts Copper, for metal parts Polycarbonate, for dolly
Connections - terminals	Brass rod terminals
Width	23.55 mm
Height	52.4 mm
Depth	1.8 mm

### Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant

Operating altitude	2000 m
Standards	IS 3854

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0418 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">End of life manual</a>
Product end of life instructions	Need no specific recycling operations