# Product datasheet
## Characteristics

# X1001WH
## Opale - 6A 1 way switch

## Main

| | |
|---|---|
| Range of product | Opale |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with central plate |
| Outlet poles configuration | 1P |
| Colour tint | White |
| Quantity per set | Set of 10 |

## Complementary

| | |
|---|---|
| Device mounting | Flush / Surface |
| Number of cables | 1 (2.5 mm² stranded)<br>1 (2.5 mm² solid)<br>3 (1.5 mm² stranded)<br>3 (1.5 mm² solid) |
| Number of modules | 1 module |
| Rated current | 6 A 220-240 V AC 50 Hz |
| Material | PC+ABS cover<br>Pa6 Base<br>Brass terminal<br>Moving contact - CuZn33<br>AgNi/Cu bimetal contact tip |
| Load type | Inductive / Resistive |
| Terminal Screw type | Captive screws |
| Height | 51 mm |
| Width | 21 mm |
| Depth | 26 mm |

## Environment

| | |
|---|---|
| Environmental characteristic | Flame retardant |
| Standards | IS-3854 1997 |
| IP degree of protection | IP20 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications