



Main

Range of product	Opale
Product or component type	Switch with indicator lamp
Device presentation	Mechanism with central plate
Colour tint	White
Quantity per set	Set of 10

Complementary

Device mounting	Flush / Surface
Actuator	Rocker
Number of cables	1 (2.5 mm ² stranded) 1 (2.5 mm ² solid) 3 (1.5 mm ² stranded) 3 (1.5 mm ² solid)
Number of modules	1 module
Rated current	16 A 220-240 V AC 50 Hz
Material	PC+ABS cover Pa6 Base Brass terminal Moving contact - CuZn33 AgNi/Cu bimetal contact tip
Load type	Inductive / Resistive
Terminal Screw type	Captive screws
Height	51 mm
Width	21 mm
Depth	26 mm

Environment

Environmental characteristic	Flame retardant
Standards	IS-3854 1997
IP degree of protection	IP20

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0840 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations