



### Main

Range of product	Opale
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Outlet poles configuration	3P with shutters
Colour tint	White
Quantity per set	Set of 10

### Complementary

Device mounting	Flush / Surface
Number of cables	1 (4 mm <sup>2</sup> stranded) 1 (4 mm <sup>2</sup> solid) 2 (2.5 mm <sup>2</sup> stranded) 2 (2.5 mm <sup>2</sup> solid)
Number of modules	2 modules
Rated current	20 A 220-240 V AC 50 Hz
Material	PC+ABS cover Polycarbonate Base Brass screw and nut Brass contact parts PA66 shutter
Load type	Inductive / Resistive
Terminal Screw type	Captive screws
Height	51 mm
Width	42 mm
Depth	30 mm

### Environment

Environmental characteristic	Flame retardant
Standards	IS 1293 1988
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0840 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations