



Main

Range of product	Opale
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Outlet poles configuration	3P with shutters
Colour tint	White
Quantity per set	Set of 10

Complementary

Device mounting	Flush / Surface
Number of cables	1 (2.5 mm ² stranded) 1 (2.5 mm ² solid) 3 (1.5 mm ² stranded) 3 (1.5 mm ² solid)
Number of modules	2 modules
Rated current	13 A 220-240 V AC 50 Hz
Material	PC+ABS cover Polycarbonate Base Brass screw and terminal Brass contact parts PA66 shutter
Load type	Inductive / Resistive
Terminal Screw type	Captive screws
Height	51 mm
Width	42 mm
Depth	29 mm

Environment

Environmental characteristic	Flame retardant
IP degree of protection	IP20

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0840 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations