

SL42 4" Direct Thermal Shipping Label Printer


- Direct thermal printing
- Up to 6IPS high speed printing with low noise
- Compact design, built-in adapter, save more space
- Printer head intensified coating and more durable
- Larger size rubber roller to prevent label sticking
- Auto label detection
- Error Reprint Technology



Larger size rubber roller to prevent label sticking



Optional Accessory: External label holder



Specification

Item		Parameter
Printing	Method	Direct Thermal
	Resolution	203dpi(8dots/mm)
	Speed Maximum	150 mm/s
	Width Maximum	108 mm
	Length Maximum	300 mm
Processor		32 bit RISC CPU
Memory	RAM	2MB
	Flash	2MB
Detection	Sensors	Label edge detection, Out of paper detection, Gap detection, Black mark detection, Cover open detection
Media	Types	Folded paper or roll paper, die-cut label, black mark paper
	Width	2"(50mm)-4.65"(118mm)
	Thickness	0.003" (60um) - 0.0087" (220um)
	External paper roll	Max OD 5" (127mm)
	External folding paper	W:100mm x L:100mm-300mm
Programming Language		TSPL
Software	Label Design	Customer can download third-party editing software for label design
	Driver	Windows 2000, XP, Vista 7, 8, 10
Resident Fonts		Full ASCII 8x16, 12x24 bitmap fonts, up to 10 times enlarge, 4 directional rotation
Code Pages		DOS437, 720, 737, 755, 775, 850, 852, 855, 856, 857, 858, 860, 862, 863, 864, 865, 866, Windows 1250, 1251, 1252, 1253, 1254, 1255, 1256, 1257, 1258, ISO8859-1, -2, -3, -4, -5, -6, -8, -9, -15



Barcode	1D	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C,
	2D	QR Code
Interfaces	Standard	USB
Control Panel		One Feed button (three colors for different three states) Tear paper from above Coordinated type of paper guiding roller Automatic paper suction from back and then positioning
Power Adapter Input		AC100V ~240V 1.5A 50/60Hz
Environment	Output	DC24V/2A
	Operation	41°F (5°C) - 104°F (40°C), 30%-85%RH
	Storage	-4°F (-20°C) - 122°F (50°C), 10%-90%RH
Physical	Dimension	220mm (L) x 120mm (W) x 108mm (T)
Characteristics	Weight	1.5kg
Optional Accessories		External 5" roll stand or folding paper box
Agency Approvals		CCC, FCC, CE



WiFi



Bluetooth



Travel



Logistic



Medical



Battery



Barcode



Windows



Android



iOS