



## ARCHITECTURAL MISCELLANEOUS

### *BUILDING & CONSTRUCTION(EXTRUDED PRODUCTS)*

Section	<b>ARCHITECTURAL</b>				
Commodity	<b>ARCHITECTURAL MISCELLANEOUS</b>				
Technique	Extrusion				
GRADE SERIES/ TEMPER	<b>Grade (USA)</b>			<b>Temper (USA)</b>	
	1000 Series – 1050/1060, 1100, EC, 2000 Series - 2014, 3000 Series – 3103. 5000 Series - 5052, 5086 6000 Series - 6101, 6063, 6061, 6351/6082, 6055 7000 Series – 7075			O, F, T <sub>3</sub> , T <sub>4</sub> , T <sub>5</sub> , T <sub>6</sub> , H21, H22, H24, H26, H28, H1, H32, H34, H36, H38	
Size	<b>Key</b>	<b>Min</b>	<b>Max</b>		
	<b>As Per Customer Request Against Drawing or Sample</b>				
Length	1000 to 3650mm				
FINISH	Mill Finish				
PACKAGE	HDPE – SEA WORTHY PACKING				
APPLICATION	Aluminium is widely used in building because of its intrinsic properties of lightness and corrosion resistance. Aluminum is used in external facades, roofs and walls, in windows and doors, in staircases, railings, shelves, and other several applications.				