



STEP EDGINGS

BUILDING & CONSTRUCTION(EXTRUDED PRODUCTS)

| | | | | | |
|----------------------|--|-------------|-------------|---|--|
| Section | ARCHITECTURAL | | | | |
| Commodity | STEP EDGINGS | | | | |
| Technique | Extrusion | | | | |
| GRADE SERIES/ TEMPER | Grade (USA) | | | Temper (USA) | |
| | 1000 Series – 1050/1060, 1100, EC, 2000 Series - 2014, 3000 Series – 3103. 5000 Series - 5052, 5086 6000 Series - 6101, 6063, 6061, 6351/6082, 6055 7000 Series – 7075 | | | 0, F, T ₃ , T ₄ , T ₅ , T ₆ , H21, H22, H24, H26, H28, H1, H32, H34, H36, H38 | |
| Size | Key | Min | Max | | |
| | A | 30 | 43 | | |
| | B | 10 | 10.2 | | |
| | C | 2.8 | 3.2 | | |
| | D | 3.5 | 3.5 | | |
| | E | 0.78 | 0.80 | | |
| | F | 0.48 | 0.60 | | |
| | As Per Customer Request Against Drawing or Sample | | | | |
| Length | 1000 to 3650mm | | | | |
| FINISH | Mill Finish | | | | |
| PACKAGE | HDPE – SEA WORTHY PACKING | | | | |
| APPLICATION | Normally used as stair tread edging or in any application where alloy serrated angle is required for anti slip protection. | | | | |