

DH-DMS26V1

High Resolution Vari-Focal Dome Camera with OSD



Main Features

- 1/3" Sony CCD
- 520 TVL High Resolution Camera
- 0.3 Lux @ F1.2
- 4~9 mm Vari-Focal Manual Iris Lens
- D-WDR/2DNR/DPC/Lens Shading/De-Moire Suppress/
Motion Detection/Privacy Region Shielded
- AGC, AWB and BLC
- CE, FCC Certified



| Feature | Specification |
|-------------------------|---------------------------------------|
| Image Sensor | 1/3" Sony CCD |
| Pixels | PAL:ICX633BK/NTSC:ICX632BK |
| Resolution | 520 TVL |
| Min. Illumination | 0.3 Lux @ F1.2 |
| S/N Ratio | more than 48 dB |
| Electronic Shutter | 1/50(60)sec-1/100,000sec |
| Flickerless Mode | ON/OFF |
| Lens | 4~9 mm manual IRIS varifocal lens |
| Gamma Correction | 0.45 |
| White Balance (AWB) | Auto (ATW1 / ATW2 / AWC→SET / Manual) |
| Gain Control (AGC) | High / Middle / Low(6dB~40dB) |
| Back Light Compensation | BLC/HLC/OFF selectable |
| Sync | Internal Sync |
| Video Output | Composite 1.0V P-P/75Ω |
| Power Supply | DC12V±10% |
| Dimensions | 130 ϕ ×100H |
| Weight | 317 |
| Operating Temperature | (-10°C~+50°C) |
| Certifications | CE, FCC Certified |