

DH-CA-DMS30

High Resolution Dome Camera with OSD



Main Features

- 1/3" Sony CCD
- 600 TVL High Resolution Camera
- 0.05 Lux (BW), 0.8 Lux (Color) / F2.0
- 3.6 mm Fixed Lens
- AGC, AES, BLC, Mirror, Privacy Masking and Motion Detection
- CE, FCC Certified



Feature	Specification
Image Sensor	1/3" Sony CCD
Pixels	NTSC:795x596, PAL:811x508
Resolution	600 TVL
Min. Illumination	0.05 Lux (BW), 0.8 Lux (Color) / F2.0
S/N Ratio	more than 50dB
Electronic Shutter	Auto:1/50(1/60)-1/100,000(Sec.)
Flickerless Mode	ON/OFF
Iris Control	Video / DC Drive / Manual
Lens	3.6 mm
Gamma Correction	0.45
White Balance (AWB)	Auto Tracking White Balance, Auto / Indoor / Outdoor / Manual / Push Auto
Gain Control (AGC)	Auto/Manual
Back Light Compensation	ON/OFF Selectable
Day & Night (ICR)	OSD Control
Sync	Internal Sync
Video Output	1Vp-p,75ohm,BNC
Special Functions	OSD
Power Supply	DC 12V
Power Consumption	1.5W
Weight	400
Operating Temperature	-10~50 °C
Certifications	CE, FCC Certified