

# InMobi Pokkt Mediation

---

## Prerequisites

- Please create account at [www.inmobi.com](http://www.inmobi.com)
- Please read instructions at <https://support.inmobi.com/monetize/integration/ios/ios-sdk-integration-guide/#getting-started> to integrate your iOS application with InMobi
- Please read instructions at <https://support.inmobi.com/monetize/integration/ios/ios-sdk-integration-guide/#creating-an-interstitial-or-native-> to show rewarded video ads in your application.
- Register your property in InMobi account/dashboard.
- Go to the Monetize tab and click the spanner icon next to your property. Your Placement ID is displayed. Copy this value and use it in the integration code.

---

## Configuration in Application

- Copy the following header files and binary from the downloaded Inmobi SDK bundle to your project.
  - libInMobi-5.x.x.a
  - IMSdk.h
  - IMBanner.h
  - IMBannerDelegate.h
  - IMInterstitial.h
  - IMInterstitialDelegate.h
  - IMNative.h
  - IMNativeDelegate.h
  - IMCustomNative.h
  - IMRequestStatus.h
  - IMCommonConstants.h

- Make sure the following frameworks are added to your Xcode project:
  - AdSupport.framework
  - AudioToolbox.framework
  - AVFoundation.framework
  - CoreLocation.framework
  - CoreTelephony.framework
  - EventKit.framework
  - EventKitUI.framework
  - MediaPlayer.framework
  - MessageUI.framework
  - Security.framework
  - Social.framework
  - StoreKit.framework
  - SystemConfiguration.framework
  - UIKit.framework
  - SafariServices.framework
  - libsqlite3.0.dylib
  - libc++.dylib
- Note: Set NSLocationWhenInUseUsageDescription flag to YES in your info.plist file

---

## Code changes

- Create a class which implements Pokkt's AdNetwork interface.
- This class should also implement InMobi Callback protocol IMInterstitialDelegate
- Pokkt SDK's PokktNetworkDelegate methods should be mapped from your newly created class methods.

- - (void)interstitialDidFinishLoading:(IMInterstitial \*)interstitial
  - - (void)interstitial:(IMInterstitial \*)interstitial didFailToLoadWithError:(IMRequestStatus \*)error
  - - (void)interstitial:(IMInterstitial \*)interstitial didFailToPresentWithError:(IMRequestStatus \*)error
  - - (void)interstitialWillPresent:(IMInterstitial \*)interstitial
  - - (void)interstitialDidPresent:(IMInterstitial \*)interstitial
  - - (void)interstitialWillDismiss:(IMInterstitial \*)interstitial
  - - (void)interstitialDidDismiss:(IMInterstitial \*)interstitial
  - - (void)userWillLeaveApplicationFromInterstitial:(IMInterstitial \*)interstitial
  - - (void)interstitial:(IMInterstitial \*)interstitial rewardActionCompletedWithRewards:(NSDictionary \*)rewards
  - - (void)interstitial:(IMInterstitial \*)interstitial didInteractWithParams:(NSDictionary \*)params
- Sample implementation of this class is included in release. InMobiNetwork.h and InmobiNetwork.m
  - Now the last part, please declare this class name in your Pokkt account Dashboard.