

TATA ACE MAGIC2

हरेक यात्रामा **magic**



उत्कृष्ट माइलेज



उत्कृष्ट वारेण्टी



देशकै सबै भन्दा ठूलो बिक्री, सर्भिस र स्पेयर पार्ट्सको संजाल



न्यूनतम मर्मत खर्च



उच्च पुनर्विक्री मूल्य

SIPRADI

SIPRADI TRADING P. LTD.

A Distributor of **TATA** Vehicles

टोल फ्री नं.: १६६००१५५७७७

८८०१५७५७७७

SPECIFICATIONS

EMISSION ENGINE

	Bharat Stage III and IV
Model:	TATA 275 IDI NA
Type and Capacity:	702 cc, 2-cylinder diesel engine
Max. Output:	16 HP @ 3200 RPM
Max. Torque:	38 NM @ 2000 RPM

DRIVELINE

Clutch:	Single plate dry friction diaphragm type (170 mm diameter)
Gearbox:	GBS 65-4/6.31
Type:	Synchromesh (4 forward gears), Sliding mesh (reverse gear)

STEERING:

Mechanical, variable ratio (20.5 to 24.5)

BRAKES

Type:	Vacuum-assisted dual circuit hydraulically activated
Front:	Disc brakes
Rear:	Drum brakes

SUSPENSION

Front:	Rigid axle with parabolic leaf spring
Rear:	Live axle with parabolic leaf spring
Shock absorber:	Hydraulic double-acting telescopic type

WHEELS AND TYRES

Tyres:	145R12 LT 8PR Radial (12 inch)
--------	--------------------------------

FUEL TANK CAPACITY:

30 litres

PERFORMANCE

Max. speed:	60 kmph
Max. gradeability:	22%
Grade restartability:	21%

DIMENSIONS (in mm)

Length (mm):	3790
Width (mm):	1500
Height (mm):	1845 (unladen)
Wheelbase (mm):	2100
Ground Clearance (mm):	160
Turning Radius:	4.3 m
Kerb Weight:	1000 kg


SEATS

Seating Capacity:	6+1 / 7+1
Seat Type:	Bucket seats - driver & co-passenger Bench seats - passenger

COLOURS AVAILABLE



Laser Red



Arctic White



Yellow

For further details, please contact:

Siprati Trading Pvt. Ltd.

An ISO 9001:2008 Certified Company
Thapathali, Kathmandu, 01-4230340

Toll Free No.: 16600155777 / 9801575777

Website: www.tatamotors.com.np



NEW FEATURE ADDITIONS



Sleek design



Stylish dashboard




Comfortable passenger cabin



Wide-angle mirrors



Mobile charger provision



Music system provision



Superior headlamp

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.