

# LOAD ON. PROFIT ON.

Presenting the all-new **LPT 1212.**



Tata LPT 1212 is the perfect cargo transport solution with higher loading capacity. Its powerful engine and higher torque let you carry more load with ease and better fuel efficiency. A heavy-duty chassis frame, best-in-class ground clearance, bigger clutch and a superior suspension ensure an easy drive, no matter how rough the roads or terrains are.



### POWERFUL & RELIABLE ENGINE

- Reliable 497 TCIC common rail engine with proven engine life and repairability
- Used across applications for over a decade
- Improved performance and better fuel efficiency
- Lower emissions
- Lower levels of noise and vibration



### BIGGER CLUTCH SIZE

- 330 mm clutch
- Efficient power transmission
- Longer durability
- Provides balance between power & efficiency
- Driving comfort with easy engagement of gears



### OPTIMUM POWER

- Engine HP: 125 ps @ 2400 rpm
- Engine torque: 400 nm @ 1300-1600 rpm
- More load-carrying capacity
- Ease of driving even at low speeds
- Optimum power output even at lower RPMs
- Lesser gear shifts while driving
- Better fuel efficiency




### BEST-IN-CLASS GROUND CLEARANCE

- Ground clearance: 245 mm
- Convenient on different terrains and road conditions




### HEAVY DUTY AXLE

- Single reduction hypoid gears
- Rear axle ratio: 5.857: 1 (41/7)



### HEAVY-DUTY CHASSIS FRAME

- Higher durability
- Excellent torsional, bending and lateral stiffness
- Channel section:
  - a. Depth - 223 mm
  - b. Flange width - 60 mm
  - c. Thickness - 7 mm



### SUPERIOR SUSPENSION

- Thicker semi-elliptical leaf spring
- Longer life
- Rear - 8 + 8 nos.
- Thickness - 15 mm



### HIGH STRENGTH DRIVE SHAFT

- Propeller shaft diameter: 90 mm
- Longer life
- Higher critical speed with lesser chances of bending



## SPECIFICATIONS

Displacement	3783
Max Engine Output	125 PS @ 2400 rpm
Max Torque	400 Nm @ 1300-1500 rpm
Clutch	Single-plate dry-friction type. 330 mm dia
Gear box	GBS 40 Synchronesh. 5 F, 1 R
Brakes	Dual-circuit, full-air S-Cam brake
Suspension	Semi-elliptical leaf springs
Wheels & Tyres	9 x 20 - 16 PR
Wheel Base	4200
Gradeability	26.4%
Load Body Length	19.3ft
Ground Clearance	245

The illustrations and photographs may show accessories and items of optional equipment that are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.