# InterMask<sup>™</sup> KN95 Protective Face Mask

P/N: 12889-001-7

InterMask<sup>TM</sup> KN95 Protective Face Masks are intended to be worn in the daily operation of the ordinary environment. It is a particle filtering half mask covering the nose, mouth & chin. It fulfils the requirements of executive standard GB2626-2006 and EN 149:2001+A1:2009.



# **Technical Data Sheet**

**Country of Origin: China** 

#### **General Information**

Parameters	Specifications
Features	This facemask is a single use item and it is Not
	Reusable for more than one work shift.
	High level of filtering efficiency in very dusty
	environments
	The mask meets the clogging resistance
	requirements.
	Classified as FFP2 NR D in EN 149:2001
	+A1:2009 standards.
	GB2626-2019 Performance Standard

### **Properties**

Characteristics	Results		
Product Type	Particle filtering half mask EN		
	149:2001+A1:2009		
	FFP2 NRD		
Inhalation	Maximum Inhalation Resistance		
Resistance	<0.6 mbar, at 95 l/m		
Exhalation	Maximum Exhalation Resistance		
Resistance	<3.0 mbar, at 160 l/m		
Raw material	latex free, non-woven		
	polypropylene, melt-blown		
	fabric, & breathable cotton fibers		
Flammability	Passed; EN 149:2001+A1:2009		
Test			
Particle	≥ 95% of particles > 0.3 micron		
filtration			
efficiency			
(PFE)			

## **Packaging Details**

Part #	Description	Packaging	Weight	Case Size
12889-001-7	InterMask™	10 pcs/polybag,	18 lbs	48x40x75 in
	KN95 Protective Face Mask	2 polybags/ dispensing		
		box; 50 dispensing		
		boxes/case		

Disclaimer

This document and the information contained herein is the property of EcoPark (S) PTE. LTD. (Ecopark) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of Ecopark products for a particular purpose or use within a particular environment. ECOPARK DISCLAIMS ALL WARRANTIES OTHER THAN WHAT HAS BEEN EXPRESSLY PROVIDED.